# BookletChart™

## Cape Henry to Currituck Beach Light

### (NOAA Chart 12207)


*A reduced scale NOAA nautical chart for small boaters. When possible, use the full size NOAA chart for navigation.*

- ☑ *Complete, reduced scale nautical chart*
- ☑ *Print at home for free*
- ☑ *Convenient size*
- ☑ *Up to date with all Notices to Mariners*
- ☑ *United States Coast Pilot excerpts*
- ☑ *Compiled by NOAA, the nation's chartmaker.*




NOAA NATIONAL OCEANIC AND ATMOSPHERIC ADMINISTRATION
DEPARTMENT OF COMMERCE

*Home Edition (not for sale)*

*Published by the*
*National Oceanic and Atmospheric Administration*
*National Ocean Service*
*Office of Coast Survey*
*www.NauticalCharts.NOAA.gov*
*301-713-2770*

## What are Nautical Charts?

Nautical charts are a fundamental tool of marine navigation. They show water depths, obstructions, buoys, other aids to navigation, and much more. The information is shown in a way that promotes safe and efficient navigation. Chart carriage is mandatory on the commercial ships that carry America's commerce. They are also used on every Navy and Coast Guard ship, fishing and passenger vessels, and are widely carried by recreational boaters.

## What is a BookletChart™?

This BookletChart is made to help recreational boaters locate themselves on the water. It has been reduced in scale for convenience, but otherwise contains all the information of the full-scale nautical chart. The bar scales have also been reduced, and are accurate when used to measure distances in this BookletChart. See the Note at the bottom of page 5 for the reduction in scale applied to this chart.

Whenever possible, use the official, full scale NOAA nautical chart for navigation. Nautical chart sales agents are listed on the Internet at http://www.NauticalCharts.NOAA.gov.

This BookletChart does NOT fulfill chart carriage requirements for regulated commercial vessels under Titles 33 and 44 of the Code of Federal Regulations.

## Notice to Mariners Correction Status

This BookletChart has been updated for chart corrections published in the U.S. Coast Guard Local Notice to Mariners, the National Geospatial Intelligence Agency Weekly Notice to Mariners, and, where applicable, the Canadian Coast Guard Notice to Mariners. Additional chart corrections have been made by NOAA in advance of their publication in a Notice to Mariners. The last Notices to Mariners applied to this chart are listed in the Note at the bottom of page 7. Coast Pilot excerpts are not being corrected.




[Coast Pilot 4, Chapter 4 excerpts]
(19) The summer resort of **Virginia Beach** is 5 miles southward of Cape Henry Light. Many high-rise buildings and two water tanks are prominent. Some of these are lighted at night. A hotel cupola, 3.4 miles south of Cape Henry Light, is distinctive.
(23) A **naval restricted area** extends northward, eastward, and southeastward from Cape Henry.
(24) A **naval prohibited area** is off Camp Pendleton, 7.4 miles southward of Cape Henry.
(25) **Danger zones of naval firing ranges** are about 8 and 9 miles southward of Cape Henry.
(26) Two radar towers and a blue water tank, 158 feet above the water, are prominent at the Dam Neck Naval Station about 9 miles southward of Cape Henry Light.
(27) **Sandbridge Beach,** 11 miles south of Cape Henry Light, has a tower and a green water tank that are prominent. There are about 3 miles of beach residences south of Sandbridge Beach.
(28) Part of Back Bay National Wildlife Refuge extends from 15 to 18.5 miles south of Cape Henry Light along The Outer Banks.
(29) **False Cape,** so called because of its resemblance to Cape Henry when approaching from south, is 22 miles southward of Cape Henry Light. Several spots with depths of 10 to 17 feet are 0.8 to 1.5 miles offshore from False Cape.
(30) Sand dunes in this area have a tendency to alternately erode and then build up again as the seasons change, generally working to the southward; they should not be depended upon as navigational marks.
(95) **Currituck Sound**, is a narrow and shoal body of water which extends for 25 miles in a north-south direction behind the barrier beach near Currituck Beach Light. The southern part of the sound is navigable for craft drawing 4 or 5 feet to the junction with Albemarle Sound, but navigation among the extensive shoals depends on local knowledge of the channels and on the level of the water. The northern part of the sound is practically unnavigable due to dense grass. There are no periodic tides in Currituck Sound; the water level depends upon the force and direction of the winds.
(97) **Back Bay** and its connections with Currituck Sound extends 10 miles northward from the northeastern end of the sound. This shoal bay is navigable only for small boats. Northward of Back Bay are shallow **Shipps Bay** and **North Bay.** Facilities with small-boat launching ramps, and some with gasoline, water, ice, and bait and tackle, are along the western shore of Back Bay.
(98) **North Landing River** extends in a north-northwesterly direction from the north end of Currituck Sound. The river is a part of the Intracoastal Waterway.

# Table of Selected Chart Notes

Corrected through NM Oct. 24/09
Corrected through LNM Oct. 13/09

HEIGHTS

Heights in feet above Mean High Water.

INTRACOASTAL WATERWAY

Use chart 12206. The depths and channel markers are not shown hereon.

INTRACOASTAL WATERWAY

Use chart 12206. The depths and channel markers are not shown hereon.

CAUTION

Temporary changes or defects in aids to navigation are not indicated on this chart. See Local Notice to Mariners.

RADAR REFLECTORS

Radar reflectors have been placed on many floating aids to navigation. Individual radar reflector identification on these aids has been omitted from this chart.

POLLUTION REPORTS

Report all spills of oil and hazardous substances to the National Response Center via 1-800-424-8802 (toll free), or to the nearest U.S. Coast Guard facility if telephone communication is impossible (33 CFR 153).

WARNING

The prudent mariner will not rely solely on any single aid to navigation, particularly on floating aids. See U.S. Coast Guard Light List and U.S. Coast Pilot for details.

CAUTION

Survey platforms, signs, pipes, piles, and stakes, some submerged, may exist along the maintained channels. Piles and platforms are not charted where they interfere with a light symbol.

CAUTION

Improved channels shown by broken lines are subject to shoaling, particularly at the edges.

AIDS TO NAVIGATION

Consult U.S. Coast Guard Light List for supplemental information concerning aids to navigation.

NOAA WEATHER RADIO BROADCASTS

The NOAA Weather Radio stations listed below provide continuous weather broadcasts. The reception range is typically 20 to 40 nautical miles from the antenna site, but can be as much as 100 nautical miles for stations at high elevations.

| | | |
|---|---|---|
| Norfolk, VA | KHB-37 | 162.550 MHz |
| Mamie, NC | WWH-26 | 162.425 MHz |

SUPPLEMENTAL INFORMATION

Consult U.S. Coast Pilot 4 for important supplemental information.

Mercator Projection
Scale 1:80,000 at Lat. 36° 39'

North American Datum of 1983
(World Geodetic System 1984)

SOUNDINGS IN FEET
AT MEAN LOWER LOW WATER

CAUTION

SUBMARINE PIPELINES AND CABLES

Charted submarine pipelines and submarine cables and submarine pipeline and cable areas are shown as:

*Pipeline Area* *Cable Area*

Additional uncharted submarine pipelines and submarine cables may exist within the area of this chart. Not all submarine pipelines and submarine cables are required to be buried, and those that were originally buried may have become exposed. Mariners should use extreme caution when operating vessels in depths of water comparable to their draft in areas where pipelines and cables may exist, and when anchoring, dragging, or trawling.

Covered wells may be marked by lighted or unlighted buoys.

NOTE S

Regulations for Ocean Dumping Sites are contained in 40 CFR, Parts 220-229. Additional information concerning the regulations and requirements for use of the sites may be obtained from the Environmental Protection Agency (EPA). See U.S. Coast Pilots appendix for addresses of EPA offices. Dumping subsequent to the survey dates may have reduced the depths shown. Lighted buoys A through F are uncharted due to frequent relocations.

HORIZONTAL DATUM

The horizontal reference datum of this chart is North American Datum of 1983 (NAD 83), which for charting purposes is considered equivalent to the World Geodetic System 1984 (WGS 84). Geographic positions referred to the North American Datum of 1927 must be corrected an average of 0.544" northward and 1.238" eastward to agree with this chart.

NOTE B

DANGER AREA

Area is open to unrestricted surface navigation but all vessels are cautioned neither to anchor, dredge, trawl, lay cables, bottom, nor conduct any other similar type of operation because of residual danger from mines on the bottom.

NOTE A

Navigation regulations are published in Chapter 2, U.S. Coast Pilot 4. Additions or revisions to Chapter 2 are published in the Notice to Mariners. Information concerning the regulations may be obtained at the Office of the Commander, 5th Coast Guard District in Portsmouth, Virginia or at the Office of the District Engineer, Corps of Engineers in Norfolk, Virginia.

Refer to charted regulation section numbers.

## LORAN-C

### GENERAL EXPLANATION

LORAN-C FREQUENCY.....100kHz
PULSE REPETITION INTERVAL
9960.....99,600 Microseconds
STATION TYPE DESIGNATORS: (Not individual station letter designators).

M ..... Master
W ..... Secondary
X ..... Secondary
Y ..... Secondary
Z ..... Secondary

EXAMPLE: 9960-X

### RATES ON THIS CHART

Loran-C correction tables published by the National Geospatial-Intelligence Agency or others should not be used with this chart. The lines of position shown have been adjusted based on survey data. Every effort has been made to meet the ¼ nautical mile accuracy criteria established by the U.S. Coast Guard. Mariners are cautioned not to rely solely on the lattices in inshore waters.

NOTE D

EMERGENCY RESTRICTED AREA

For the latest information regarding the regulations of any emergency restricted area, contact the Army Corps of Engineers, Norfolk District, Regulatory Branch at (757) 201-7653/7652.

NOTE C

TRAFFIC SEPARATION SCHEME

The traffic separation scheme is designed to aid in the prevention of collisions at the approaches to Chesapeake Bay and does not supersede or alter the applicable Rules of the Road.

The RECOMMENDED routes for entering and departing from Chesapeake Bay are overprinted on this chart. The Northeast Approach is marked by a tinted magenta line centered on a line of fairway buoys which separates the courses of inbound and outbound vessels. Vessels should leave all buoys on their port hand.

It is RECOMMENDED that the following ships use the Southern Approach deep-water route when bound for Chesapeake Bay from sea or to sea from Chesapeake Bay: Deep-draft ships, drafts defined as 42 feet/12.8 meters or greater in fresh water, and naval aircraft carriers. Ships drawing less than 42 feet/12.8 meters may use the deep-water route when, in their master's judgment, the effects of ship characteristics, its speed, and prevailing environmental conditions may cause the draft of the ship to equal or exceed 42 feet/12.8 meters.

It is RECOMMENDED that a ship using the deep-water route:

Announce its intention on VHF-FM channel 16 as it approaches Chesapeake Bay Southern Approach Lighted Whistle Buoy "CB" on the south end, or Chesapeake Bay Entrance Lighted Whistle Buoy "CH", on the north end of the route;

Avoid, as far as practicable, overtaking other ships operating in the deep-water route;

Keep as near to the outer limit of the route which lies on the starboard side as is safe and practicable.

All other ships approaching the Chesapeake Bay traffic separation scheme should use the appropriate inbound or outbound traffic lane of the traffic separation scheme.

Traffic within the precautionary area may consist of vessels operating between Thimble Shoal and Chesapeake Channels and one of the established traffic lanes. Mariners are advised to exercise extreme care in navigating within this area. The normal Pilot Boarding Area is outlined by a magenta band.

Additional information can be obtained at nauticalcharts.noaa.gov.

AUTHORITIES

Hydrography and topography by the National Ocean Service, Coast Survey, with additional data from the Corps of Engineers, Geological Survey, and U.S. Coast Guard.

HURRICANES AND TROPICAL STORMS

Hurricanes, tropical storms and other major storms may cause considerable damage to marine structures, aids to navigation and moored vessels, resulting in submerged debris in unknown locations.

Charted soundings, channel depths and shoreline may not reflect actual conditions following these storms. Fixed aids to navigation may have been damaged or destroyed. Buoys may have been moved from their charted positions, damaged, sunk, extinguished or otherwise made inoperative. Mariners should not rely upon the position or operation of an aid to navigation. Wrecks and submerged obstructions may have been displaced from charted locations. Pipelines may have become uncovered or moved.

Mariners are urged to exercise extreme caution and are requested to report aids to navigation discrepancies and hazards to navigation to the nearest United States Coast Guard unit.

CAUTION

This chart has been corrected from the Notice to Mariners (NM) published weekly by the National Geospatial-Intelligence Agency and the Local Notice to Mariners (LNM) issued periodically by each U.S. Coast Guard district to the dates shown in the lower left hand corner. Chart updates corrected from Notice to Mariners published after the dates shown in the lower left hand corner are available at nauticalcharts.noaa.gov.

This nautical chart has been designed to promote safe navigation. The National Ocean Service encourages users to submit corrections, additions, or comments for improving this chart to the Chief, Marine Chart Division (N/CS2), National Ocean Service, NOAA, Silver Spring, Maryland 20910-3282.

TIDAL INFORMATION

| PLACE | | Height referred to datum of soundings (MLLW) | | |
|---|---|---|---|---|
| NAME | (LAT/LONG) | Mean Higher High Water | Mean High Water | Mean Low Water |
| | | feet | feet | feet |
| Norfolk | 36°51'N/76°18'W | 3.1 | 2.9 | 0.1 |
| Cape Henry | 36°56'N/76°00'W | 3.5 | 3.2 | 0.1 |
| Virginia Beach | 36°51'N/75°58'W | 3.9 | 3.6 | 0.2 |

Dashes (- - -) located in datum columns indicate unavailable datum values for a tide station. Real-time water levels, tide predictions, and tidal current predictions are available on the Internet from http://tidesandcurrents.noaa.gov.

(Sep 2009)

ABBREVIATIONS (For complete list of Symbols and Abbreviations, see Chart No. 1.)

Aids to Navigation (lights are white unless otherwise indicated):

AERO aeronautical
Al alternating
B black
Bn beacon
C can
DIA diaphone
F fixed
Fl flashing
G green
IQ interrupted quick
Iso isophase
LT HO lighthouse
M nautical mile
m minutes
MICRO TR microwave tower
Mkr marker
Mo morse code
N nun
OBSC obscured
Oc occulting
Or orange
Q quick
R red
Ra Ref radar reflector
R Bn radiobeacon
R TR radio tower
Rot rotating
s seconds
SEC sector
St M statute miles
VQ very quick
W white
WHIS whistle
Y yellow

Bottom characteristics:

Blds boulders
bk broken
Cy clay
Co coral
G gravel
Grs grass
gy gray
h hard
M mud
Oys oysters
Rk rock
S sand
so soft
Sh shells
sy sticky

Miscellaneous:

AUTH authorized
ED existence doubtful
Obstn obstruction
PA position approximate
PD position doubtful
Rep reported
Subm submerged

(21) Wreck, rock, obstruction, or shoal swept clear to the depth indicated.
(2) Rocks that cover and uncover, with heights in feet above datum of soundings.
COLREGS: International Regulations for Preventing Collisions at Sea, 1972.
Demarcation lines are shown thus: — — — —

NOTE X

Within the 12-nautical mile Territorial Sea, established by Presidential Proclamation, some Federal laws apply. The Three Nautical Mile Line, previously identified as the outer limit of the territorial sea, is retained as it continues to depict the jurisdictional limit of the other laws. The 9-nautical mile Natural Resource Boundary off the Gulf coast of Florida, Texas, and Puerto Rico, and the Three Nautical Mile Line elsewhere remain in most cases the inner limit of Federal fisheries jurisdiction and the outer limit of the jurisdiction of the states. The 24-nautical mile Contiguous Zone and the 200-nautical mile Exclusive Economic Zone were established by Presidential Proclamation. Unless fixed by treaty or the U.S. Supreme Court, these maritime limits are subject to modification.

PRINT-ON-DEMAND CHARTS

NOAA and its partner, OceanGrafix, offer this chart updated weekly by NOAA for Notices to Mariners and critical corrections. Charts are printed when ordered using Print-on-Demand technology. New Editions are available 5-8 weeks before their release as traditional NOAA charts. Ask your chart agent about Print-on-Demand charts or contact NOAA at 1-800-584-4683, http://NauticalCharts.gov, help@NauticalCharts.gov, or OceanGrafix at 1-877-56CHART, http://OceanGrafix.com, or help@OceanGrafix.com.

# SOUNDINGS IN FEET




Joins page 8



North

Printed at reduced scale. ~~SCALE 1:80,000~~ See Note on page 5.

Nautical Miles
1 0 1 2 3 4 5 6 7

Yards
1000 0 2000 4000 6000 8000 10000




SOURCE DIAGRAM

The outlined areas represent the limits of the most recent hydrographic survey information that has been evaluated for charting. Surveys have been banded in this diagram by date and type of survey. Channels maintained by the U.S. Army Corps of Engineers are periodically resurveyed and are not shown on this diagram. Refer to Chapter 1, United States Coast Pilot.

| SOURCE | | | |
|---|---|---|---|
| A | 1990-2006 | NOS Surveys | full bottom coverage |
| B2 | 1970-1989 | NOS Surveys | partial bottom coverage |
| B4 | 1900-1939 | NOS Surveys | partial bottom coverage |
| B5 | Pre-1900 | NOS Surveys | partial bottom coverage |
| e | | Chart 12222 | |




This BookletChart was reduced to 70% of the original chart scale. The new scale is 1:114286. Barscales have also been reduced and are accurate when used to measure distances in this BookletChart.






North

Printed at reduced scale. ~~SCALE 1:80,000~~

Nautical Miles 1 0 1 2 3 4 5 6 7

Yards 1000 0 2000 4000 6000 8000 10000

See Note on page 5.




This BookletChart has been updated with: Coast Guard Local Notice To Mariners: 0810 2/23/2010,
NGA Weekly Notice to Mariners: 1010 3/6/2010,
Canadian Coast Guard Notice to Mariners: n/a .

Joins page 4

NOAA WEATHER RADIO BROADCASTS

The NOAA Weather Radio stations listed below provide continuous weather broadcasts. The reception range is typically 20 to 40 nautical miles from the antenna site, but can be as much as 100 nautical miles for stations at high elevations.

| | | |
|---|---|---|
| Norfolk, VA | KHB-37 | 162.550 MHz |
| Manie, NC | WWH-26 | 162.425 MHz |

CAUTION

SUBMARINE PIPELINES AND CABLES

Charted submarine pipelines and submarine cables and submarine pipeline and cable areas are shown as:

*Pipeline Area* *Cable Area*

Additional uncharted submarine pipelines and submarine cables may exist within the area of this chart. Not all submarine pipelines and submarine cables are required to be buried, and those that were originally buried may have become exposed. Mariners should use extreme caution when operating vessels in depths of water comparable to their draft in areas where pipelines and cables may exist, and when anchoring, dragging, or trawling.

Covered wells may be marked by lighted or unlighted buoys.

INTRACOASTAL WATERWAY

Use chart 12206. The depths and channel markers are not shown hereon.

NOTE C

TRAFFIC SEPARATION SCHEME

The traffic separation scheme is designed to aid in the prevention of collisions at the approaches to Chesapeake Bay and does not supersede or alter the applicable Rules of the Road.

The RECOMMENDED routes for entering and departing from Chesapeake Bay are overprinted on this chart. The Northeast Approach is marked by a tinted magenta line centered on a line of fairway buoys which separates the courses of inbound and outbound vessels. Vessels should leave all buoys on their port hand.

It is RECOMMENDED that the following ships use the Southern Approach deep-water route when bound for Chesapeake Bay from sea or to sea from Chesapeake Bay: Deep-draft ships, drafts defined as 42 feet/12.8 meters or greater in fresh water, and naval aircraft carriers. Ships drawing less than 42 feet/12.8 meters may use the deep-water route when, in their master's judgment, the effects of ship characteristics, its speed, and prevailing environmental conditions may cause the draft of the ship to equal or exceed 42 feet/12.8 meters.

It is RECOMMENDED that a ship using the deep-water route:

Announce its intention on VHF-FM channel 16 as it approaches Chesapeake Bay Southern Approach Lighted Whistle Buoy "CB" on the south end, or Chesapeake Bay Entrance Lighted Whistle Buoy "CH", on the north end of the route;

Avoid, as far as practicable, overtaking other ships operating in the deep-water route;

Keep as near to the outer limit of the route which lies on the starboard side as is safe and practicable.

All other ships approaching the Chesapeake Bay traffic separation scheme should use the appropriate inbound or outbound traffic lane of the traffic separation scheme.

Traffic within the precautionary area may consist of vessels operating between Thimble Shoal and Chesapeake Channels and one of the established traffic lanes. Mariners are advised to exercise extreme care in navigating within this area. The normal Pilot Boarding Area is outlined by a magenta band.

LORAN-C

GENERAL EXPLANATION

LORAN-C FREQUENCY.....100kHz
PULSE REPETITION INTERVAL
9960.....99,600 Microseconds
STATION TYPE DESIGNATORS: (Not individual station letter designators).
M..... Master
W..... Secondary
X..... Secondary
Y..... Secondary
Z..... Secondary

EXAMPLE: 9960-X

RATES ON THIS CHART

Loran-C correction tables published by the National Geospatial-Intelligence Agency or others should not be used with this chart. The lines of position shown have been adjusted based on survey data. Every effort has been made to meet the ¼ nautical mile accuracy criteria established by the U.S. Coast Guard. Mariners are cautioned not to rely solely on the lattices in inshore waters.

GREAT DISMAL SWAMP

GREAT DISMAL SWAMP CANAL (see chart 12206)

Deep Creek Lock

Deep Cr

Millville

New Mill Cr

Marsh Great Bridge

Fentress

Enohla Farms

Hickory

St Brides

Northwest

Feeder Ditch

OVHD PWR CAB

45'

40'

35'

Joins page 12

Printed at reduced scale. ~~SCALE 1:80,000~~

See Note on page 5.

Nautical Miles 1 0 1 2 3 4 5 6 7

Yards 1000 0 2000 4000 6000 8000 10000

North


Joins page 5
Joins page 10
Joins page 13
B5
B4
B4
B5
B5
36°
30°
20°
10°
75°
50°
40°
Princess Anne
Marsh
Lake Tecu
Sandbridge Beach
TR
TK
Ashville Bridge Creek
Pungo
INTRACOASTAL WATERWAY (see note)
Albemarle - Chesapeake Canal
OVHD PWR CAB
North Ldg
Cow Cr
Haynes Cr
West Neck Creek
West Ldg
Pocaty River
Pleasant Ridge
Marsh
North Bay
Muddy Cr
Porpoise Pt
Shipps Bay
Great Narrows
Long Island
Charity Neck
Back Bay
Little Narrows
Redhead Bay
Drum Pt
Nawney Cr
Pungo Ferry
TANK
Creeds
Blackwater Cr
Millclam Cr
Spoil Area
Muncen
Munden Pt
Subm Silos
Snake Cr
Walnut I Cr
Walke Pt
Pollitory Pt
Public Ldg
North End
Morse Point
Green Pt
Marsh
VIRGINIA
NORTH CAROLINA
Northwest River
Shingle Landing Creek
Moyock
Sandy Pt
Gibbs Pt
Faraby
The Causeway
Corys
Great Marsh
Back Creek
MACKAY ISLAND NATIONAL WILDLIFE REFUGE
MAGNETIC
VAR 10°45 W (2008)
ANNUAL INCREASE 1




10

North

Printed at reduced scale. ~~SCALE 1:80,000~~

Nautical Miles 1 0 1 2 3 4 5 6 7

Yards 1000 0 2000 4000 6000 8000 10000

See Note on page 5.


Joins page 7
ATLANTIC OCEAN
45'
40'
35'
Obstn
Wk
Rep 1977
PA
(52 ft rcp)
ULATED NAVIGATION AREA
165.501 (see note A)
LOCAL MAGNETIC DISTURBANCE
(see note)
Joins page 15

Joins page 8

Loran-C correction tables published by the National Geospatial-Intelligence Agency or others should not be used with this chart. The lines of position shown have been adjusted based on survey data. Every effort has been made to meet the ¼ nautical mile accuracy criter a established by the U.S. Coast Guard. Mariners are cautioned not to rely solely on the lattices in inshore waters.




LORAN LINEAR INTERPOLATOR

NOTE A

Navigation regulations are published in Chapter 2, U.S. Coast Pilot 4. Additions or revisions to Chapter 2 are published in the Notice to Mariners. Information concerning the regulations may be obtained at the Office of the Commander, 5th Coast Guard District in Portsmouth, Virginia or at the Office of the District Engineer, Corps of Engineers in Norfolk, Virginia.

Refer to charted regulation section numbers.

NOTE B

DANGER AREA

Area is open to unrestricted surface navigation but all vessels are cautioned neither to anchor, dredge, trawl, lay cables, bottom, nor conduct any other similar type of operation because of residual danger from mines on the bottom.

NOTE D

EMERGENCY RESTRICTED AREA

For the latest information regarding the regulations of any emergency restricted area, contact the Army Corps of Engineers, Norfolk District, Regulatory Branch at (757) 201 7653/7652.

NOTE S

Regulations for Ocean Dumping Sites are contained in 40 CFR, Parts 220-229. Additional information concerning the regulations and requirements for use of the sites may be obtained from the Environmental Protection Agency (EPA). See U.S. Coast Pilots appendix for addresses of EPA offices. Dumping subsequent to the survey dates may have reduced the depths shown. Lighted buoys A through F are uncharted due to frequent relocations.

ABBREVIATIONS (For complete list of Symbols and Abbreviations, see Chart No. 1.)

Aids to Navigation (lights are white unless otherwise indicated):

| | | | |
|---|---|---|---|
| AERO aeronautical | G green | Mo morse code | R TR radio tower |
| Al alternating | IQ interrupted quick | N nun | Ret rotating |
| B black | Iso isophase | OBSC obscured | s seconds |
| Bn beacon | LT HO lighthouse | Oc occulting | SEC sector |
| C can | M nautical mile | Or orange | St M statute miles |
| DIA diaphone | m minutes | Q quick | VQ very quick |
| F fixed | MICRO TR microwave tower | R red | W white |
| Fl flashing | Mkr marker | Ra Ref radar reflector | WHS whistle |
| | | R Bn radiobeacon | Y yellow |

Bottom characteristics:

| | | | | | |
|---|---|---|---|---|---|
| Blds boulders | Co coral | gy gray | Cys oysters | so soft | |
| bk broken | G gravel | h hard | Rk rock | Sh shells | |
| Cy clay | Grs grass | M mud | S sand | sy sticky | |

Miscellaneous:

| | | | |
|---|---|---|---|
| AUTH authorized | Obstn obstruction | PD position doubtful | Subm submerged |
| ED existence doubtful | PA position approximate | Rep reported | |

(21) Wreck, rock, obstruction, or shoal swept clear to the depth indicated.

(2) Rocks that cover and uncover, with heights in feet above datum of soundings.

COLREGS: International Regulations for Preventing Collisions at Sea, 1972.

Demarcation lines are shown thus: ———

HEIGHTS

Heights in feet above Mean High Water.

SUPPLEMENTAL INFORMATION

Consult U.S. Coast Pilot 4 for important supplemental information.

CAUTION

Improved channels shown by broken lines are subject to shoaling, particularly at the edges.

CAUTION

Survey platforms, signs, pipes, piles, and stakes, some submerged, may exist along the maintained channels. Piles and platforms are not charted where they interfere with a light symbol.

LOCAL MAGNETIC DISTURBANCE

Differences of as much as 6° from the normal variation have been observed 3 to 17 nautical miles offshore from Cape Henry to Currituck Beach Light.

TIDAL INFORMATION

| PLACE | | Height referred to datum o | |
|---|---|---|---|
| NAME | (LAT/LONG) | Mean Higher High Water | Mean High Wat |
| | | feet | feet |
| Norfolk | 36°51'N/76°18'W | 3.1 | 2.9 |
| Cape Henry | 36°56'N/76°00'W | 3.5 | 3.2 |
| Virginia Beach | 36°51'N/75°59'W | 3.9 | 3.6 |

Dashes (- - -) located in datum columns indicate unavailable datum values for a tide station. Re tide predictions, and tidal current predictions are available on the Internet from http://tidesandcu

(Sep 2009)



CONTINUED ON CHART 12206

THE NATION'S CHARTMAKER SINCE 1807

UNITED STATES - EAST COAS

VIRGINIA - NORTH CAROLI

# CAPE HENRY TO CURRITUC

Mercator Projection
Scale 1:80,000 at Lat. 36° 39'

North American Datum of 1983
(World Geodetic System 1984)

SOUNDINGS IN FEET
AT MEAN LOWER LOW WATER

Additional information can be obtained at nauticalcharts.n

AUTHORITIES

Hydrography and topography by the National Ocean Servi Survey, with additional data from the Corps of Engineers, G Survey, and U.S. Coast Guard.

HORIZONTAL DATUM

The horizontal reference datum of this chart is No American Datum of 1983 (NAD 83), which for charting purpo is considered equivalent to the World Geodetic System 19 (WGS 84). Geographic positions referred to the North Ameri Datum of 1927 must be corrected an average of 0.5 northward and 1.238" eastward to agree with this chart.

22nd Ed., Oct. /09 ■
12207
LORAN-C OVERPRINTED

Corrected through NM Oct. 24/09
Corrected through LNM Oct. 13/09

CAUTION

This chart has been corrected from the Notice to Mariners (NM) published weekly by the National Geospatial-Intelligence Agency and the Local Notice to Mariners (LNM) issued periodically by each U.S. Coast Guard district to the dates shown in the lower left hand corner. Chart updates corrected from Notice to Mariners published after the dates shown in the lower left hand corner are available at nauticalcharts.noaa.gov.

This nautical chart has been designed to promote safe navigation. The National Ocean Service encourages users to submit corrections, additions, or comments fo improving this chart to the Chief, Marine Chart Division (N/CS2), National Ocean Service, NOAA, Silver Spring, Maryland 20910-3282.



North

Printed at reduced scale. ~~SCALE 1:80,000~~ See Note on page 5.

Nautical Miles: 1 0 1 2 3 4 5 6 7

Yards: 1000 0 2000 4000 6000 8000 10000




| Mean Low Water |
|---|
| feet |
| 0.1 |
| 0.1 |
| 0.2 |

Real-time water levels, ...currents.noaa.gov.

PRINT-ON-DEMAND CHARTS

NOAA and its partner, OceanGrafix, offer this chart updated weekly by NOAA for Notices to Mariners and critical corrections. Charts are printed when ordered using Print-on-Demand technology. New Editions are available 5-8 weeks before their release as traditional NOAA charts. Ask your chart agent about Print-on-Demand charts or contact NOAA at 1-800-584-4683, http://NauticalCharts.gov, help@NauticalCharts.gov, or OceanGrafix at 1-877-56CHART, http://OceanGrafix.com, or help@OceanGrafix.com.

Published at Washington, D.C.
U.S. DEPARTMENT OF COMMERCE
NATIONAL OCEANIC AND ATMOSPHERIC ADMINISTRATION
NATIONAL OCEAN SERVICE
COAST SURVEY




Published at Washington, D.C.
U.S. DEPARTMENT OF COMMERCE
OCEANIC AND ATMOSPHERIC ADMINISTRATION
NATIONAL OCEAN SERVICE
COAST SURVEY

SOUNDINGS IN FEET

| FATHOMS | 1 |
|---|---|
| FEET | 6 |
| METERS | 1 2 |



North

Printed at reduced scale. ~~SCALE 1:80,000~~

Nautical Miles: 1 0 1 2 3 4 5 6 7

Yards: 1000 0 2000 4000 6000 8000 10000

See Note on page 5.

Joins page 11




Cape Henry to Currituck Beach Light

SOUNDINGS IN FEET - SCALE 1:80,000

# 12207

LORAN-C OVERPRINTED

ED NO. 22
NSN 7642014010298 NGA REFERENCE NO. 12AHA12207

# EMERGENCY INFORMATION

**VHF Marine Radio channels for use on the waterways:**

**Channel 6** – Inter-ship safety communications.
**Channel 9** – Communications between boats and ship-to-coast.
**Channel 13** – Navigation purposes at bridges, locks, and harbors.
**Channel 16 – Emergency, distress and safety calls** to Coast Guard and others, and to initiate calls to other vessels. Contact the other vessel, agree to another channel, and then switch.
**Channel 22A** – Calls between the Coast Guard and the public. Severe weather warnings, hazards to navigation and safety warnings are broadcast here.
**Channels 68, 69, 71, 72 & 78A** – Recreational boat channels.

**Distress Call Procedures**

1. Make sure radio is on.
2. Select Channel 16.
3. Press/Hold the transmit button.
4. Clearly say: "MAYDAY, MAYDAY, MAYDAY."
5. Also give: Vessel Name and/or Description; Position and/or Location; Nature of Emergency; Number of People on Board.
6. Release transmit button.
7. Wait for 10 seconds – If no response Repeat MAYDAY Call.

**HAVE ALL PERSONS PUT ON LIFE JACKETS !!**

**Mobile Phones** – Call 911 for water rescue.
**Coast Guard Cape Charles** – 757-331-2000
**Coast Guard Portsmouth** – 757-483-8526/8527
**Coast Guard Elizabeth City** – 919-335-6085/6086
**Coast Guard Oregon Inlet** – 252-441-6260
**NC Wildlife Resources Commission** – 800-662-7137

**NOAA Weather Radio** – 162.400 MHz, 162.425 MHz, 162.450 MHz, 162.475 MHz, 162.500 MHz, 162.525 MHz, 162.550 MHz.

**Getting and Giving Help** – Signal other boaters using visual distress signals (flares, orange flag, lights, arm signals); whistles; horns; and on your VHF radio. You are required by law to help boaters in trouble. Respond to distress signals, but do not endanger yourself.

*NOAA, The Nation's Chartmaker*

# NOAA CHARTING PUBLICATIONS

Official NOAA Nautical Charts – NOAA surveys and charts the national and territorial waters of the U.S, including the Great Lakes. We produce over 1,000 traditional nautical charts covering 3.4 million square nautical miles. Carriage of official NOAA charts is mandatory on the commercial ships that carry our commerce. They are used on every Navy and Coast Guard ship, fishing and passenger vessels, and are widely carried by recreational boaters. NOAA charts are available from official chart agents listed at: www.NauticalCharts.NOAA.gov.

Official Print-on-Demand Nautical Charts – These full-scale NOAA charts are updated weekly by NOAA for all Notice to Mariner corrections. They have additional information added in the margin to supplement the chart. Print-on-Demand charts meet all federal chart carriage regulations for charts and updating. Produced under a public/private partnership between NOAA and OceanGrafix, LLC, suppliers of these premium charts are listed at www.OceanGrafix.com.

Official Electronic Navigational Charts (NOAA ENCs®) – ENCs are digital files of each chart's features and their attributes for use in computer-based navigation systems. ENCs comply with standards of the International Hydrographic Organization. ENCs and their updates are available for free from NOAA at www.NauticalCharts.NOAA.gov.

Official Raster Navigational Charts (NOAA RNCs™) – RNCs are geo-referenced digital pictures of NOAA's charts that are suitable for use in computer-based navigation systems. RNCs comply with standards of the International Hydrographic Organization. RNCs and their updates are available for free from NOAA at www.NauticalCharts.NOAA.gov.

Official BookletCharts™ – BookletCharts™ are reduced scale NOAA charts organized in page-sized pieces. The "Home Edition" can be downloaded from NOAA for free and printed. The Internet address is www.NauticalCharts.gov/bookletcharts.

Official PocketCharts™ – PocketCharts™ are for beginning recreational boaters to use for planning and locating, but not for real navigation. Measuring a convenient 13" by 19", they have a 1/3 scale chart on one side, and safety, boating, and educational information on the reverse. They can be purchased at retail outlets and on the Internet.

Official U.S. Coast Pilot® – The Coast Pilots are 9 text volumes containing information important to navigators such as channel descriptions, port facilities, anchorages, bridge and cable clearances, currents, prominent features, weather, dangers, and Federal Regulations. They supplement the charts and are available from NOAA chart agents or may be downloaded for free at www.NauticalCharts.NOAA.gov.

Official On-Line Chart Viewer – All NOAA nautical charts are viewable here on-line using any Internet browser. Each chart is up-to-date with the most recent Notices to Mariners. Use these on-line charts as a ready reference or planning tool. The Internet address is www.NauticalCharts.gov/viewer.

Official Nautical Chart Catalogs – Large format, regional catalogs are available for free from official chart agents. Page size, state catalogs are posted on the Internet and can be printed at home for free. Go to http://NauticalCharts.NOAA.gov/mcd/ccatalogs.htm.

Internet Sites: www.NauticalCharts.NOAA.gov, www.NOAA.gov, www.TidesandCurrents.NOAA.gov, www.NOS.NOAA.gov.